

LRM120

Finishing mower for loader



- /// Maintenance-free blade bearings
- /// Custom mounts available for all types of loaders
- /// Ribbed V-belt
- /// Rear roller scraper
- /// Easy belt tensioning

The LRM120 finishing mower features a fully hydraulic drive system and a durable construction, ensuring strong performance and reliability. Designed for use with loaders, it uses a system where three blades are driven by a hydraulic motor. This design increases mowing efficiency and delivers an excellent cutting result.

LIGHT

Pressure (Mpa) 16
Working width (cm) 120

Product features

Cutter Disc Configuration

The cutter disc system is equipped with three cutter discs to ensure stable operation and uniform rotational cutting. A labyrinth seal provides reliable sealing performance, while the lifetime maintenance-free bearing supports consistent operation with minimal servicing requirements. Made of high-strength manganese steel, the blade offers strong wear resistance and good cutting performance.



LRM Multi-Wedge Belt

The LRM Multi-Wedge Belt is designed to deliver efficient power transmission and improve overall transmission efficiency. With strong wear resistance, high-temperature resistance, and a long service life, it supports reliable performance under demanding conditions. The use of standard belt pulleys enhances stability, while the design also allows for easy installation and replacement, helping to keep maintenance costs low.



Technical specifications

	LIGHT
Model	LRM120
Working width (mm)	1200
Transport width (mm)	1249
Oil flow (l/min)	30
Pressure (Mpa)	16
Weight (kg)	132
Mounting position	Loader
Cutting diameter (mm)	< 40

Product Features	
Maintenance-free blade bearings	•
Custom mounts available	•
3 cutter disc configuration	•
LRM Multi-Wedge Belt	•

AWON Machinery

Professor Lorentzweg 16
5144 NP Waalwijk
The Netherlands

+31 (0)416 – 745 338
info@awonmachinery.com
www.awonmachinery.com

